




eukula[®]
WOOD.FLOOR.LOVE

DISCOVER
**WOOD.
FLOOR.
LOVE.**

www.eukula.com

eukula
WOOD.FLOOR.LOVE

eukula hardwax oil+

Easy to apply, fast drying



Advantages of eukula hardwax oil+

- 01** Very low consumption
- 02** 1-day system, due to fast drying
- 03** Great coverage, warm look, natural feel
- 04** Good penetration, increased water resistance, elastic film
- 05** Very wear and stain resistant
- 06** Easy roller application
- 07** Can be combined with additives in a modular system
- 08** Suitable for coating children's toys according to EN 71, part 3
- 09** Tested according to DIN 53160, welding and saliva fastness
- 10** Meets the requirements of BGR 181, DIN 51130, slip class R9
- 11** Meets the requirements according to BGR 181, DIN 51130, slip class R10 with antislip R10 additive

A premium finish with natural raw materials

Many customers want an oil finish that is as natural as possible and at the same time a hard-wearing oil finish for their high-quality wood or cork floors. With the new eukula hardwax oil+ system you have the perfect products to fulfil your customers' wishes.

The eukula hardwax oil+ system offers wood floor professionals easy application, combined with high-quality ingredients and particularly short drying times.

The perfect package for the professional.



easy application



natural look



fast drying



suitable for toys



The deep-penetrating and fast-drying hard wax oil from eukula was specially developed for the initial treatment and renovation of wooden surfaces. Thanks to its fast drying, you get a hard-wearing protective layer with two applications in only one day on all sanded wood, parquet and cork floors as well as OSB boards.

Perfect for first-class results



eukula hardwax oil+

Layer-forming, deeply penetrating oil based on vegetable oils for easy-care surfaces with a natural look

The eukula hardwax oil+ is available in ultra mat and satin in container sizes of 5l, 2.5l and 1l.

 **natural look**

 **fast drying**

 **suitable for toys**



eukula master FS


For professional use only

Reactive cross linker. eukula hardwax oil+ in combination with eukula master FS becomes a 2-component oil of the highest quality.

Improves oil hardening properties and surface resistance.

 **solvent-free**

 **2 part component for all eukula oils**


 **environmentally friendly, as 100% solvent free**



eukula hardwax antislip add R10

For particularly slip-resistant results:

The antislip R10 additive increases the structure of the product, thereby creating a slip resistance class of R10 according to BGR 181 and DIN 51130. Without the addition of this additive, the floor treated with eukula hardwax oil+ corresponds to a slip resistance class R9.

 **increased slip resistance**

 **easy application**




eukula hardwax nature add

For a very natural look

The nature additive has the effect of reducing the colour intensity of the product. This gives your floor a particularly natural finish „as if untreated“. For particularly easy application, the additive is provided in liquid form.

 **brightening**

 **for light woods**

 **natural look**




eukula color oil FS

Pigmented natural oil-based deep impregnation for wood and cork floors in residential and commercial areas

The eukula color oil FS is available in 12 standard colours and 40 „on demand“ colour formulations. The oils can be mixed with each other to create individual looks.

 **solvent-free**

 **long open time**

 **can be lacquered over**





eukula refresher classic

For the care and refreshment of impregnated oiled floors

Freshens up dull, particularly stressed and intensively cleaned oil surfaces.

also available in white

 **film-forming**

 **contains waxes**

 **mild smell**

The use of eukula hardwax oil+ in the modular system

The eukula hardwax oil+ is an all-rounder for every type of building - for normally frequented floors and in combination with the eukula master FS also for heavily frequented floors, e.g. in commercial areas. eukula offers you every desired effect: whether for coloured surfaces, a natural look or increased slip resistance.

	For normal wear oil surface	Oil surface with raw wood effect	Oil surface with white effect	Oil surface with slip resistance of R10	Coloured oil surface
eukula hardwax oil+	Step 1 + 2 2 x 50 ml/m ²	Step 2 1 x 60 - 70 ml/m ²	-	Step 1 1 x 50 ml/m ²	Step 2 1 x 60 - 70 ml/m ²
eukula color oil FS 2-part (incl. eukula master FS)	-	-	-	-	Step 1 1 x 30-50 ml/m ² fill/polish
eukula hardwax nature add	-	Step 1 1 x 35 ml/m ² HWO + nature add 10:1	Step 1 + 2 2 x 50 ml/m ² HWO + nature add 10:1	-	-
eukula hardwax antislip add R10	Step 2 can be applied if slip resistance of R10 is required. 1 x 50 ml/m ² + antislip R10 add 10:1				
eukula master FS	For heavily used surfaces, add 10:1 in all coats.				



Recommended accessories

Hardwax oil roller & handle 10 cm

Special roller for small areas and edges

Hardwax oil roller & handle 25 cm

Special roller for our hardwax oils



download now

How to properly clean and care for hard wax oiled floors – simply explained step by step:
eukula.com/en/care-instructions



Member of
DGNB
Deutsche Gesellschaft für Nachhaltiges Bauen
German Sustainable Building Council

eukula® a brand of **Dr. Schutz® GROUP**

D

Dr. Schutz International
Holbeinstraße 17
D-53175 Bonn, Germany
☎ +49 (0) 228 / 953 52 - 0
✉ export@dr-schutz.com

US

Sam Jamison
8701 Torresdale Ave, Suite P
Philadelphia PA 19136, USA
☎ 001/877 272 4889
✉ sam@dr-schutz.us

UK

Guy White
Unit 24 Anglo Business Park
Smeaton Close | Aylesbury
Bucks HP19 8UP, UK
☎ +44 7587 053634
✉ guy.white@drschutz.co.uk

Ireland

Paul O'Reardon
35 Pic Du Jer Park
Ballinlough | Cork, Ireland
☎ 00353/877 678 388
✉ drschutzireland@gmail.com

🌐 www.eukula.com

📱 [/eukula_de](https://www.instagram.com/eukula_de)

JOIN US

📺 [/eukula_int](https://www.youtube.com/eukula_int)