





















Overview eukula oil system

Find the best structure for your wooden floor




















WOOD.FLOOR.LOVE – made with  in Germany

	Oil Open purist	Oil-wax combination Bee lover	Oil with wax finish Silky gloss	Colour oil Play of colours
1.	 <p>Prepare/sand surfaces according to the state of the art and the rules of the trade. Grout with fill 101 - grouting solution. It is important that the sanding pattern is as free of sanding marks as possible.</p>			
2.	 <p>Moisten the sanded floor (25-50 ml/m² pure water). Spray on/wipe up - surface must be fully wetted once - wait for complete visible drying.</p>			
2a.	 <p>ALTERNATIVELY, the eukula conditioners can also be used for step 2 to create a special coloured effect. Wipe on - 16 hours drying time - build up with the desired impregnation system.</p>			
	 <p>With the following treatment methods floors are protected for medium- to heavy-traffic areas.</p>			
3.	 <p>oil 1FS ~ 50 ml/m² (until saturation) 18 - 24 hours</p>	 <p>oil 2+ FS ~ 50 ml/m² (until saturation) 18 - 24 hours</p>	 <p>oil 1FS ~ 50 ml/m² (until saturation) 18 - 24 hours</p>	 <p>color oil FS ~ 50 ml/m² 18 - 24 hours</p>
4.	 <p>Completely buff off/polish out excess with Normal Pad white or beige.</p>			
5.	 <p>care oil ~ 25 ml/m² 18 - 24 hours until usable</p>	 <p>refresher refresher classic ~ 25 ml/m² 18 - 24 hours until usable</p>	 <p>refresher refresher classic ~ 25 ml/m² 18 - 24 hours until usable</p>	 <p>care oil ~ 25 ml/m² 18 - 24 hours until usable</p>
6.	 <p>Completely buff off/polish out excess with Normal Pad white or beige.</p>			
	 <p>open-pored, natural and plant-based pure oil impregnation</p>	 <p>open-pored, natural plant-based oil-wax combination with bee and carnauba waxes</p>	 <p>open-pored, natural and plant-based pure oil impregnation with wax finish</p>	 <p>coloured, open-pored, natural and plant-based pure oil impregnation</p>
	 <p>To achieve maximum durability, add master FS to the oil systems in a mixing ratio of 10:1.</p>			

More detailed information can be found on eukula.com in our current product information and our technical information sheets.

*Load capacity ( light,  medium,  strong/very strong,  extremely strong)  solvent-free product

OIL

	Color oil wax finish Coloured with topping	Colour oil - hard wax oil Art and film	Oil - hard wax oil Impregnating evenly	Hard wax oil Plant-based simple
1.	 <p>Prepare/sand surfaces according to the state of the art and the rules of the trade. Grout with fill 101 - grouting solution. It is important that the sanding pattern is as free of sanding marks as possible.</p>			
2.	 <p>Moisten the sanded floor (25-50 ml/m² pure water). Spray on/wipe up - surface must be fully wetted once - wait for complete visible drying.</p>			
2a.	 <p>ALTERNATIVELY, the eukula conditioners can also be used for step 2 to create a special coloured effect. Wipe on - 16 hours drying time - build up with the desired impregnation system.</p>			
	 <p>With the following treatment methods floors are protected for medium- to heavy-traffic areas.</p>			
3.	 <p>color oil FS ~ 50 ml/m² 18 - 24 hours</p>	 <p>color oil FS + master FS ~ 50 ml/m² 18 - 24 hours</p>	 <p>oil 1FS + master FS ~ 50 ml/m² (until saturation) 18 - 24 hours</p>	 <p>hardwax oil+ 50 - 60 ml/m² 6 - 8 hours until second application</p>
4.	 <p>Completely buff off/polish out excess with Normal Pad white or beige.</p>			
5.	 <p>refresher refresher classic ~ 25 ml/m² 18 - 24 hours until usable</p>	 <p>hardwax oil+ 60 - 80 ml/m² 18 - 24 hours until usable</p>	 <p>hardwax oil+ 60 - 80 ml/m² 18 - 24 hours until usable</p>	 <p>hardwax oil+ 50 - 60 ml/m² 18 - 24 hours until usable</p>
6.	 <p>Completely buff off/ polish out excess with Normal Pad white or beige.</p>			
	 <p>coloured, open-pored, natural and plant-based pure oil impregnation with wax finish</p>	 <p>coloured, plant-based, natural impregnation with the protection of an evenly film-forming hard wax oil</p>	 <p>natural, plant-based impregnation with the protection of an evenly film-forming hard wax oil</p>	 <p>more durable, plant-based and uniform film-forming hard wax oil structure</p>
	 <p>To achieve maximum durability, add master FS to the oil systems in a mixing ratio of 10:1. In the case of a hard wax oil build-up, we also recommend a further coat to increase the film thickness.</p>			

More detailed information can be found on eukula.com in our current product information and our technical information sheets.

OIL